



## ORLEN OIL ULTOR CI-4 20W-50

### General features

High-quality mineral engine oil for the lubrication of heavy-duty diesel engines with and without turbocharging. Recommended especially for standard change intervals in engines of tractors, trucks, vans, buses and other heavy-duty vehicles as long as the manufacturer allows the use of oil of this viscosity and quality class.

### Application

ORLEN OIL Ultor CI-4 20W-50 is mainly compatible with engines meeting EURO 3 and earlier emission standards. Ensures the highest level of drive unit culture (by preventing sludge and carbon deposits and wear of lubricated components). Conventional SAPS level - not suitable for use in vehicles equipped with exhaust after-treatment systems in the form of particulate filters.

### Quality class

API: CI-4

### Viscosity grad

SAE: 10W-40

### Physical and chemical parameters:

Parameters	Unit	Typial values
Kinematic viscosity at 100°C	mm <sup>2</sup> /s	17,5-20,5
Pour point	°C	-24
Flash-point	°C	215
Viscosity index	-	120
CCS structural viscosity at - 15°C, not higher than	mPa*s	9500
Sulfated ash content, not higher than	% m/m	2,0

The above figures are typical of those obtained with normal production batch, they are not a technical specification, due to continuous development of the product, they may change.

Version 1 / 2024-04-17